

Handling

Dropping, throwing, striking with a forklift or otherwise mishandling can result in damage. You may not notice the damage until you have paper jams or other feeding problems. Avoid touching the toner-receptive laminated area of Trilar™ products.

Storage

Store your tabs off the floor on shelves or pallets to avoid moisture absorption, extreme temperatures, and humidity. Temperature and humidity are critical factors in how DocuCopy® Copier Tabs perform in your copier or printer.

Do not open boxes until you are ready to load into your copier or printer. Store remaining loose sheets in a resealable plastic bag. Do not store in your machine's paper trays.

Our product is best stored at 72°F / 22°C with 45% - 55% relative humidity.

Paper Conditioning

Paper conditioning is the process of allowing the product to acclimate to your production environment and will result in better performance.

To condition your product, store in its original, sealed packaging in your production area to allow it to acclimate to the environmental conditions. As a rule, condition DocuCopy® Copier Tabs for three to seven days for best results.

For tab templates and additional information go to www.docucopyproducts.com

Please refer to your equipment manual for proper running information.

Also from



Reinforced Multipurpose Papers

*Contact us for samples and info:
info@docucopyproducts.com*

*The reinforcement strip
is compressed into the
sheet for flat stacking
and effortless printing.*

*Available in various
formats.*